

Attorney Docket No. 5577-314
Application Serial No. 09/652,056
Filed: August 31, 2000
Page 2

Listing of Claims:

The listing of claims will replace all prior versions and listings of claims in the application:

Claims 1-9 (Canceled).

10. (Previously Presented) A computer program product embodied on one or more computer-readable media, the computer program product adapted for encoding a document in an extensible machine-oriented structured notation and comprising:

computer-readable program code means for encoding a node count representing a count of nodes in the document;

computer-readable program code means for encoding a node specification for each of the nodes, further comprising:

computer-readable program code means for encoding a node name;

computer-readable program code means for encoding a child list specifying index values of zero or more nodes which are children of the node;

computer-readable program code means for encoding an attribute list specifying zero or more attribute pair references for attributes of the node, each attribute pair reference comprising an attribute name and an attribute value; and

computer-readable program code means for encoding a node value specification, which is empty if the node has no value;

computer-readable program code means for encoding a data buffer containing attribute names and attribute values referenced from the attribute lists and node values referenced from the node value specifications; and

computer-readable program code means for storing the encoded node count, the encoded node specifications, and the encoded data buffer as the encoded document in memory or writing the encoded document to one or more storage media.

Attorney Docket No. 5577-314
Application Serial No. 09/652,056
Filed: August 31, 2000
Page 3

11. (Previously Presented) A computer program product embodied on one or more computer-readable media, the computer program product adapted for processing a document encoded in an extensible machine-oriented structured notation and comprising:

computer-readable program code means for parsing the document, further comprising:

computer-readable program code means for parsing a node count representing a count of nodes in the document;

computer-readable program code means for parsing a node specification for each of the nodes, further comprising:

computer-readable program code means for parsing a node name;

computer-readable program code means for parsing a child list specifying index values of zero or more nodes which are children of the node;

computer-readable program code means for parsing an attribute list specifying zero or more attribute pair references for attributes of the node, each attribute pair reference comprising an attribute name and an attribute value; and

computer-readable program code means for parsing a node value specification, which is empty if the node has no value; and

computer-readable program code means for parsing a data buffer containing attribute names and attribute values referenced from the attribute lists and node values referenced from the node value specifications; and

computer-readable program code means for using the parsed document as input for the processing.

12. (Previously Presented) A computer program product embodied on one or more computer-readable media, the computer program product adapted for converting an input document encoded in an extensible human-friendly extensible markup language ("XML") to an output document encoded in a machine-oriented extensible markup language ("mXML") and comprising:

Attorney Docket No. 5577-314
Application Serial No. 09/652,056
Filed: August 31, 2000
Page 4

computer-readable program code means for creating a document tree representation of the input document;

computer-readable program code means for obtaining a node count representing a count of nodes in the document tree representation;

computer-readable program code means for writing the node count to an mXML buffer;

computer-readable program code means for traversing each node in the document tree representation and generating a corresponding node specification in the mXML buffer, further comprising:

computer-readable program code means for generating a node name;

computer-readable program code means for generating an attribute list specifying zero or more attribute pair references for attributes of the node, each attribute pair reference comprising an attribute name and an attribute value;

computer-readable program code means for generating a child list specifying index values of zero or more nodes which are children of the node; and

computer-readable program code means for generating a node value specification, which is empty if the node has no value;

computer-readable program code means for generating a data buffer containing attribute names and attribute values referenced from the attribute lists and node values referenced from the node value specifications; and

computer-readable program code means for appending the data buffer to the mXML buffer to form the output document.

13. (Previously Presented) The computer program product according to Claim 12, wherein the computer-readable program code means for generating each attribute pair reference further comprises computer-readable program code means for generating a starting name position, a name length, a starting value position, and a value length.

Attorney Docket No. 5577-314
Application Serial No. 09/652,056
Filed: August 31, 2000
Page 5

14. (Original) The computer program product according to Claim 13, wherein the starting name position and starting value position are relative to a beginning of the data buffer.

15. (Original) The computer program product according to Claim 13, wherein the starting name position and starting value position are relative to a beginning of the output document.

16. (Original) The computer program product according to Claim 12, wherein the node value specification specifies a starting value position and a value length.

17. (Original) The computer program product according to Claim 15, wherein the starting value position is relative to a beginning of the data buffer.

18. (Previously Presented) The computer program product according to Claim 15, wherein the starting value position is relative to a beginning of the output document.

19. (Previously Presented) The computer program product according to Claim 12, wherein the computer-readable program code means for generating each attribute pair reference further comprises computer-readable program code means for generating a starting name position, an ending name position, a starting value position, and an ending value position.

20. (Original) The computer program product according to Claim 12, wherein the node value specification specifies a starting value position and an ending value position.

Claims 21-31 (Canceled).

Attorney Docket No. 5577-314
Application Serial No. 09/652,056
Filed: August 31, 2000
Page 6

32. (Previously Presented) A method for encoding a document in an extensible machine-oriented structured notation, comprising the steps of:

- encoding a node count representing a count of nodes in the document;
- encoding a node specification for each of the nodes, further comprising the steps of:
 - encoding a node name;
 - encoding a child list specifying index values of zero or more nodes which are children of the node;
 - encoding an attribute list specifying zero or more attribute pair references for attributes of the node, each attribute pair reference comprising an attribute name and an attribute value; and
 - encoding a node value specification, which is empty if the node has no value;
- encoding a data buffer containing attribute names and attribute values referenced from the attribute lists and node values referenced from the node value specifications; and
- storing the encoded node count, the encoded node specifications, and the encoded data buffer as the encoded document in memory or writing the encoded document to one or more storage media.

33. (Previously Presented) A method for processing a document encoded in an extensible machine-oriented structured notation, comprising the steps of:

- parsing the document, further comprising the steps of:
 - parsing a node count representing a count of nodes in the document;
 - parsing a node specification for each of the nodes, further comprising the steps of:
 - parsing a node name;
 - parsing a child list specifying index values of zero or more nodes which are children of the node;
 - parsing an attribute list specifying zero or more attribute pair references for attributes of the node, each attribute pair reference comprising an attribute name and an

Attorney Docket No. 5577-314
Application Serial No. 09/652,056
Filed: August 31, 2000
Page 7
attribute value; and

 parsing a node value specification, which is empty if the node has no value; and

 parsing a data buffer containing attribute names and attribute values referenced from the attribute lists and node values referenced from the node value specifications; and
 using the parsed document as input for the processing.

34. (Previously Presented) A method for converting an input document encoded in an extensible human-friendly extensible markup language ("XML") to an output document encoded in a machine-oriented extensible markup language ("mXML"), comprising the steps of:

 creating a document tree representation of the input document;

 obtaining a node count representing a count of nodes in the document tree representation;

 writing the node count to an mXML buffer;

 traversing each node in the document tree representation and generating a corresponding node specification in the mXML buffer, further comprising the steps of:

 generating a node name;

 generating an attribute list specifying zero or more attribute pair references for attributes of the node, each attribute pair reference comprising an attribute name and an attribute value;

 generating a child list specifying index values of zero or more nodes which are children of the node; and

 generating a node value specification, which is empty if the node has no value;

 generating a data buffer containing attribute names and attribute values referenced from the attribute lists and node values referenced from the node value specifications; and

 appending the data buffer to the mXML buffer to form the output document.

35. (Previously Presented) The method according to Claim 34, wherein the step of generating each attribute pair reference further comprises the step of generating a starting name

Attorney Docket No. 5577-314

Application Serial No. 09/652,056

Filed: August 31, 2000

Page 8

position, a name length, a starting value position, and a value length.

36. (Original) The method according to Claim 35, wherein the starting name position and starting value position are relative to a beginning of the data buffer.

37. (Original): The method according to Claim 35, wherein the starting name position and starting value position are relative to a beginning of the output document.

38. (Original): The method according to Claim 34, wherein the node value specification specifies a starting value position and a value length.

39. (Original): The method according to Claim 37, wherein the starting value position is relative to a beginning of the data buffer.

40. (Previously Presented): The method according to Claim 37, wherein the starting value position is relative to a beginning of the output document.

41. (Previously Presented): The method according to Claim 34, wherein the step of generating each attribute pair reference further comprises the step of generating a starting name position, an ending name position, a starting value position, and an ending value position.

42. (Original): The method according to Claim 34, wherein the node value specification specifies a starting value position and an ending value position.

Claim 43 (Canceled).

44. (Original): A method for encoding a document in an extensible machine-oriented structured notation, comprising the steps of:

Attorney Docket No. 5577-314
Application Serial No. 09/652,056
Filed: August 31, 2000
Page 9

- encoding a node count representing a count of nodes in the document;
- encoding a node specification for each of the nodes, further comprising the steps of:
 - encoding a node name;
 - encoding a child list specifying index values of zero or more nodes which are children of the node; and
 - encoding a node value specification, which is empty if the node has no value;
- encoding a data buffer containing node values referenced from the node value specifications; and
- storing the encoded node count, the encoded node specifications, and the encoded data buffer as the encoded document in memory or writing the encoded document to one or more storage media.